

Two Inch Modular Flooring

www.biketrack.com

Bike Track®, Inc.
P.O. Box 235
Woodstock, VT 05091

Toll-free Tel. 888 663-8537

Tel. (802) 457-3275
Fax: (802) 457-3704

E mail: info@biketrack.com

GSA Federal Supply Service
Contractor

GSA Contract: GS-07F-0273K



Approved as TMSS Program
accessory



NSNs

5680-01-553-8745
PN: BTS-ICMS, flooring sheet
with integrated cable manage-
ment, color sand

5680-01-553-8740
PN: BTS-NICMS, flooring
sheet without integrated cable
management, color sand

Bike Track® (patented) Two Inch ICM Flooring (BTS-ICM)

4 ft x 3.5 ft sheet provides in-
floor installation of computer,
communication, and power
cables in all types of tents and
shelters.

**Designed for use in tactical
operations centers, command
posts, and forward operating
bases**

Design puts channels right in
the panel

- Eliminates need for separate
wire channel component
- Distributes cable throughout
entire shelter

Each 4 ft x 3.5 ft flooring sheet
has 2 channels running length-
wise and 1 across width, with a
total of 12 access points where
cables can be routed to surface
of floor. ICM flooring allows
cable and wire to be distributed
throughout entire shelter area
with multiple access points.
Channel covers snap into place
and are interchangeable.



Bike Track® (patented) Two Inch Flooring (BTS-NICM)

Our standard 4 ft x 3.5 ft floor-
ing sheet for use where cable
management is not required.



Bike Track® ICM and NICM Two Inch Flooring is ideal for rough & muddy conditions.

- Tent Floors
 - TOCs
 - LSA/Living spaces
 - Field hospitals
- Temporary Walkways
- Vehicle Maintenance

Bike Track® ICM and NICM Two Inch Flooring is:

- Easy to carry and install
- Easy to pack and ship
- Fast, easy, tool-free
installation & strike
- Follows contours of terrain
- No loose parts
- High strength to weight ratio
- Easily configured into wide
variety of layouts
- Supports light vehicles

Two Inch Modular Flooring

Two Inch Modular Flooring Product Data

Dimensions: (nominal)

2" ICM Flooring sheets:
4 ft x 3.5 ft x 2 inch high
(48 in x 42 in x 2 in)

overlapping traction arcs
raised 1/8 inch above surface

3/8 inch drain holes

Weight:
40 lbs per sheet

Shipping:
1,317 lbs per pallet
Each loaded pallet is 32 sheets
(448 sf of flooring).
48 in x 42 in x 75 inches high
(87.5 cubic feet)

2" NICM Flooring sheets:
4 ft x 3.5 ft x 2 inch high
(48 in x 42 in x 2 in)

overlapping traction arcs
raised 1/8 inch above surface

3/8 inch drain holes

Weight:
34 lbs per sheet

Shipping:
1,128 lbs per pallet
Each loaded pallet is 32 sheets
(448 sf of flooring).
48 in x 42 in x 75 inches high
(87.5 cubic feet)

Material:
High density polyethylene

Color:
Sand, Black

Installation:

Flooring factory pre-assembled 4 ft x 3.5 ft sheets. Each sheet consists of two 48 inch x 21 inch panels with connectors, allowing for rapid self-aligning assembly.

Installation requires no electricity, tools, nails, fasteners, or specialized training.

Sheets may be rapidly disassembled for use as single panels or for shipment in tight spaces.

Warranty:

Flooring is warranted by the manufacturer against structural failure due to splitting, cracking or damage caused by insects, rot, corrosion or fungal decay for a period of 5 years from date of purchase. The manufacturer will replace any sheet that fails to perform to its original function due to any of the above conditions when installed and used in accordance with manufacturer's specifications.

Maintenance:

Water wash or sweep periodically to remove accumulated debris if desired.

Web site:

For more floor information:
www.biketrack.com

Made in the USA

